



TS15AF64AA1XEXX

Flow meter with electronic EMR3 register

TS15A, 1 1/2"

Anodized Aluminum, Electronic

- Only two moving parts
- No metal to metal contact in chamber or bearings
- Internal pulser = Gland-less meter design
- Patented 'Wave Form' oval gear design
- Low differential pressure for maximum flow

Specifications

- **Nominal Capacity with standard LV rotors**

To 1500 SSU visc. :	60 GPM	} <i>NTEP</i> 5:1 turn-down <i>Industrial to 30:1 turn-down</i>
To 300 cP viscosity :	230 lpm	
To 300 cP viscosity :	14 m³/h	
- **Pressure Rating**
 - Meter & Strainer** : 400 PSI at 100°F = 28 BAR at 40°C
 - Air Elim & Valves** : 150 PSI at 100°F = 10 BAR at 40°C
- **Temperature Rating** *See note under Signal Conditioners*
 - Design W Assy.** : -40°F to +257°F = -40°C to +125°C
 - ATEX listing** : -4°F to +140°F = -20°C to +60°C
 - Design F Assy.** : Same, *subject to register temperature limits!*
- **Viscosity**
 - With LV rotors : 100% capacity to 1,500 SSU (300 cP).
 - With HV rotors : 100% capacity to 5,000 SSU (1000 cP),
reduced capacity to 1,500,000 SSU (350,000 cP).
- **1 1/2" Connections** Bolted companion flanges with NPT or BSP port.
 - Optional : Bolted welding flanges, anodized aluminum
 - Bolted welding flanges, carbon steel
 - Bolted 150# RF ANSI adaptors, carbon steel
- **Materials** **100% Non-Ferrous**
 - Case : Anodized aluminum
 - Gears : PPS with carbon bearings, PTFE bearings opt.
 - Posts : HC303SS
 - Seals : Viton™ standard, PTFE optional.
 - Flanges : Anodized aluminum std., carbon steel optional.
- **Pulser** : **Hall Effect Quadrature**,
5V reg or 6-12V non-reg; pls consult for 24V DC.
- **K Factor** : Nominal 1013 PPG (267.6 ppl) on 1 cP viscosity,
Opt. with SCL : EL0300-3-13C = 100 PPG (26.5 ppl)
EL0300-3-18C = 10 PPL (37.85 PPG)

Meter Performance

- **Linearity**
 - Over 5:1 turn-down from max. capacity: ±0.175%
 - Over 10:1 turn-down from max. capacity: ±0.25%
 - Over 30:1 turn-down from max. capacity: ±0.5%
- **Repeatability** 0.05% or better under constant conditions
- **Approvals** Custody Transfer approvals are liquid specific.
W&M approval in the US & Canada*.
* Canada: W&M approval of pulser is pending.
- **Flow Meter** CE mark.
- **Pulser & SCL** **Intrinsically Safe**, UL & cUL listed,
SCL also EEx ia ATEX
when powered through approved barrier.
- **Pulser encl.** II 2G Ex d IIA T4, -20°C <T_a<+60°C,
ATEX, IEC Ex & IP65

Registration, Signals & Accessories

- **Electronic registers:**
Tuthill electronic flow meters will support most common electronic registers & controllers. Available through Tuthill:
 - **ELNC** W&M register for stationary service
 - **EMR³** W&M register for stationary or truck service
 - **PC58** Totalizer/Rate meter (non-W&M)
- **Signal Conditioners:**
 - **EL0300** SCL Scaler, Calibrator and/or Linearizer.
 - **EL6630** PIA-300 amplifier for remote register (to 2,500' = 750 m)
 - **PC58** with optional 4-20 mA signal or multi-point calibration.
- **NOTE:** *If EL0300 is used in place of EL0304, max liquid temperature = 185°F (85°C). For higher temperatures, mount remote from flow meter in a separate encl.*
- **Accessories**
 - Inlet strainer for flow meter protection
 - Air eliminator mounted on strainer
 - Backpressure valve for enhanced air elimination
 - Air Check Valve on flow meter outlet side

Tuthill Transfer Systems Phone: 800-634-2695
8825 Aviation Drive, Fax: 800-866-4861
Fort Wayne, IN 46809 USA E-mail: fillrite@tuthill.com



ISO 9001:2000 Certified

International offices:
Europe, Middle East & Africa - UK Office
Mexico (North)
Mexico (South)/Caribbean/Centr. America
South America
Australia/Pacific Rim
China

Phone	Fax
+44 (115) 932-5226	+44 (115) 932-2526
+52 (81) 8303-0025	+52 (81) 8303-6334
+52 (55) 5370-2626	+52 (55) 5370-0602
+54 (11) 4116-2830	+54 (11) 4116-2835
+61 (3) 9726-2900	+61 (3) 9725-2663
+86 (21) 6917-1999	+86 (21) 6917-2162

